

Technical Data

ROCOL®

Performance you can trust

SAFE STEP® Strong Bond

Part Code: 43541
Pack Size: 500 ml

No of Pages	03
Issue No	05
Date	5/13
Ref	SBTD

Description

SAFE STEP® Strong Bond is a single pack, synthetic adhesive solution used to prime rigid or porous surfaces prior to the application of SAFE STEP® Tapes, pre-cut Treads.



Technical Data (Typical)

Colour:	Translucent white
Appearance:	Viscous tacky liquid
Chemical Type:	Acrylonitrile/Butadiene co-polymer based adhesive containing reinforcing and tackifying resins
Specific Gravity:	0.9
Maximum Bond Strength Achieved:	After 2-7 days
Theoretical Coverage Per Pack:	2.5m ²
Shelf Life:	12 months
Flash Point:	-18°C
Storage Conditions:	Store in a cool, dry, well ventilated place between 10-25°C, away from direct sunlight and sources of ignition.
Solids Content:	30%
Viscosity:	100 poise
Flammability	Highly Flammable
Tack Life:	1-3 minutes

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

Technical Data

ROCOL®

Performance you can trust

Heat Resistance:	-40 to +80 °C
Application Temperature:	Above 5 °C

Application

The surfaces to be primed must be dry and free from dust or loose material. If the area is heavily contaminated with oil or grease this should be removed with solvent or an industrial de-greaser.

When bonding non-porous, smooth or glossy surfaces, abrade the surface prior to the application of SAFE STEP® Strong Bond. Apply a thin, even coating of the adhesive by brush over an area slightly larger than required for the tape or panel.

Allow the adhesive to dry for about 20 minutes or until the adhesive film no longer transfers to the fingertip before positioning the slip resistant product.

Laying

Remove the backing paper and accurately position over the adhesive. Start laying at one end and using firm pressure work towards the other end, without trapping air bubbles. A hard rubber or wooden roller may be of assistance. Should there be any trapped air bubbles, these can be punctured and pressed down.

Once the SAFE STEP® Tape, Tread is in place, it is immediately ready for use.

Safe Step® Strong Bond and Edge Sealer Consumption Guide

Description	Product Code	Pack Size	500ml Strong Bond Tins Required (P/C 43541)	100ml Edge Sealer Tubes Required (P/C 43542)
SAFE STEP® Standard Tape				
25mm x 18.25m	43530	Single Roll	1	4
50mm x 18.25m	43531	Single Roll	1	4
100mm x 18.25m	43532	Single Roll	1	4
150mm x 18.25m	43533	Single Roll	1	4
SAFE STEP® Treads				
150mm x 600mm	43535	Pack of 10	1	2
	43534	Pack of 50	2	8
SAFE STEP® Hi-Vis Tape				
50mm x 18.25m	43540	Single Roll	1	4
SAFE STEP® Neutral Tape				
50mm x 18.25m	43539	Single Roll	1	4
SAFE STEP® Aqua Tape				
50mm x 18.25m	43538	Single Roll	Not to be used in conjunction with Strong Bond or Edge Sealer.	
SAFE STEP® Hazard Tape				
50mm x 18.25m	43547	Single Roll	1	4
SAFE STEP® Luminescent Tape				
50mm x 18.25m	43546	Single Roll	1	4

T +44 (0) 113 232 2600
 F +44 (0) 113 232 2740
 E customer-service@rocol.com
 www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
 Certificate No. FM 12448



BS EN ISO 14001
 Certificate No. EMS 67596



OHSAS 18001
 Certificate No. OHS 78173



INVESTOR IN PEOPLE

Technical Data

ROCOL®

Performance you can trust

Coverage Rates (Typical)

Strong Bond 2.5m² per 500ml tin
Edge Sealer 10m per 100ml tube

Chemical Resistance*

Water	Good
Oil, Petrol and Kerosene	Good (will not withstand prolonged immersion)
Alcohols	Good
Ketones and Esters	Poor
Dilute Acid	Good
Dilute Alkali	Good

* Incidental contact

Limitations

SAFE STEP® Strong Bond and Edge Sealer should not be used with SAFE STEP® Aqua Tape.

Health & Safety

Refer to Safety Data Sheet before use. If further copies are required or for further information, please contact us at the address below:

Safety Data Sheets – Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL® contact.

Disclaimer: The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which may affect the use and performance of our products, for this reason it is given without responsibility.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE