## **Technical Data**



#### Performance you can trust

## **Spatter Release Spray**

#### **Product Overview**

Spatter Release Spray has been formulated to allow easy removal of weld spatter from metal surfaces, nozzles, jigs and fixtures.

#### **Features and Benefits**

- Heat resistant barrier film that prevents the adhesion of weld spatter.
- Non silicone does not affect subsequent galvanising or paint operations.
- Will not interfere with weld formation.
- Non corrosive.
- Water washable.
- Biodegradable.

#### Directions for Storage and Use

- Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.
- If stored in accordance with the above guidelines, shelf life is 3 years from date of manufacture.
- Hold as near upright as possible whilst spraying. Apply a thin even film from a distance of 20-25 cm (8-10 inches) to the area near where the weld is to be made.
- Spatter can be easily removed from the work surfaces by wiping with a cloth or from the welding nozzle by tapping it on the side of the bench.

#### Pack Sizes

Pack Size	Part Code
400 mL	66080

T +44 (0) 113 232 2600 F +44 [0] 113 232 2740 E customer-service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS



ROCOL A division of TW Ltd









# **Technical Data**



#### Performance you can trust

### **Spatter Release Spray**

#### **Typical Properties**

Property	Result
Appearance	Aerosol dispensing clear liquid
Odour	Characteristic
Propellant	Dimethyl ether
Flammability	Non-flammable
Base Fluid	Water

Values quoted above are typical and do not constitute a specification.

#### Safety Data Sheets

Safety data sheets are available for download from our website <a href="www.rocol.com">www.rocol.com</a> or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue 12-09

T +44 (0) 113 232 2600

**F** +44 (0) 113 232 2740

 $\textbf{E} \ \text{customer-service} \\ \textbf{Grocol.com}$ 

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

BS EN ISO Certificate No. I







ROCOL A division of TW Ltd