Technical Data



Performance you can trust

ULTRAGUARD® AF

Non-silicone Antifoam

ULTRAGUARD® AF is a non-silicone antifoam designed for the treatment of all types of water mix metal working fluids. It contains a blend of high molecular weight polyglycol derivatives and water.

Features

- Effectively controls excessive foaming.
- Economic in use high dilution.
- Suitable for all types of water mix metalworking fluids.
- Silicone free.

Directions for Use

Add 1 part ULTRAGUARD® AF to 10000 parts of the fluid which requires de-foaming. The antifoam should be added to about 10 litres of emulsion and thoroughly stirred before adding to the machine sump.

Alternatively it may be added directly to the sump. provided there is sufficient agitation to disperse the

Should the foam persist, a second dose may be added.

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of TW Ltd











The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility

Technical Data



Performance you can trust

ULTRAGUARD® AF

| Appearance | White milky dispersion |
|-------------------------|---|
| рН | 7.0 |
| Density at 20°C | 1.00 g/cm ³ |
| | |
| Storage | Store at normal ambient temperature (5 to 30°C) |
| | |
| Pack Sizes – Part Codes | 1 ltr - 52074 |

Date: Jan-09

T +44 (0) 113 232 2600 **F** +44 (0) 113 232 2740

E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL ROCOL A division of TW Ltd









