

Performance you can trust

ULTRAGUARD® BX Bactericide Additive

ULTRAGUARD® BX is a biocide additive that can be safely used with all mineral soluble, semi-synthetic and synthetic water mix metalworking fluids. It is designed to give long lasting protection against bacterial activity and thus maintain fluid efficiency, improve working conditions and reduce operating costs.

Features

- Broad spectrum activity.
- Simple and easy to use.
- Reduces disposal and fluid replacement costs.
- Eliminates objectionable odours due to microbial growth.
- Promotes healthier working conditions.
- Prevents loss of cutting fluid performance caused by microbial degradation.

Directions for Use

Simply add ULTRAGUARD® BX to the cutting fluid in the sump at the rate of 1 part ULTRAGUARD® BX to 1000 parts water. The treatment may need to be repeated at 4 weekly intervals, but care must be taken not to exceed recommended dosage.

Appearance	Pale yellow liquid
pH	6.0 – 8.0 at 1000:1 dilution
Density at 20°C	1.14 g/cm ³
Storage	Store at normal ambient temperature (5 to 30°C)
Pack Sizes – Part Codes	1 ltr - 52084

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.