

Performance you can trust

## ULTRAGUARD® FX Fungicide Additive

**ULTRAGUARD® FX is a fungicide additive that can be used with all types of water mix metalworking fluids. It is formulated to eliminate fungus and prevent the formation of fungal growths which can cause blockages and lead to costly downtime.**

### Features

- Simple and easy to use.
- Eliminates fungal growths.
- Prevents blockages caused by fungal growths.
- Promotes healthier working conditions.
- Reduces disposal and fluid replacement costs.

### Directions for Use

Simply add ULTRAGUARD® FX to the cutting fluid in the sump at the rate of 1 part ULTRAGUARD® FX to 1000 parts water. The treatment may need to be repeated at 4 to 8 weekly intervals, but care must be taken not to exceed recommended dosage.

<b>Appearance</b>	Pale brown liquid
<b>pH</b>	6.0 – 8.0 at 1000:1 dilution
<b>Density at 20°C</b>	1.03 g/cm <sup>3</sup>
<b>Storage</b>	Store at normal ambient temperature (5 to 30°C)
<b>Pack Sizes – Part Codes</b>	1 ltr - 52094

Date: Jan-09

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.